

ACRYCLEAR HS EXTRA FAST ZA 50

*



**2004/42/IIB
e(840)600**

ACRYCLEAR HS EXTRA FAST ZA 50 is a 2K extrafast air drying clearcoat, (AIR DRY tecnologia) ANTI-SCRATCH, compliant with EC directive 2004/42/CE.

Thanks to its features it is suitable for:

- spot e large repair
- application both on mat solvent base and on water-soluble base
- very good resistance to light and to weather
- no lens effect
- energy saving (NO BAKING)
- higher productivity

application

mixing ratio

1 : 1 by volume – 100% by weight



ACRYDUR ST HS QA 2300

large area

ACRYDUR FAST HS QA 2310

spot repair

pot – life

2 hours at 25°C

application



thinness at 20°C
application viscosity

ready for use
16 seconds DIN4



spray nozzle
spraying pressure

1,3 mm
2 bar



number of coats

2

film thickness

35 – 45 micron

drying

air drying at 20°C

QA 2300 ST HS

QA 2310 FAST HS



dust free

10 minutes

5 minutes

dry for handling

50 minutes

30 minutes

*.PICTUREGRAPH LEGENDA

2004/42 Reference to the CE law

IIBe Annex, Table and Category of product

(840) Limit value of VOC with reference to the category of product

600 Maximum VOC content of the product ready for the use

180327

The information given in this technical data sheet is based on present scientific and technical knowledge and thus do not exempt the customer to test the suitability of our products for the use and for the intended purposes.

EP vernici s.r.l.

Via Roma,12 I-48027 Solarolo (RA) tel.+39 0546 53322 fax +39 0546 53323 email: laboratorio@epvernici.it www.epvernici.it

