

## MASTIC ALLUMINIUM EMZ 125

\*



**2004/42/IIB  
b(250)250**

MASTIC ALLUMINIO EMZ 125 is a putty that is based on polyester resins and aluminium. Putty knife application like a normal putty. Very good adhesion and high resistance to high temperatures. MASTIC ALLUMINIO EMZ 125 can be used in car refinish instead of tin welding, in foundry to remove and to fill fusion faults, in repair shops to close cracked cylinder blocks or bored radiators.

Thanks to its features it is particularly suitable for:

- general supports as sanded steel
- cast iron

### substrate pre-treatment



sand and degrease carefully

### application

#### method of application



by spatula

#### mixing ratio



2 – 2,5 %

#### pot – life

4 – 6 minutes at 20°C

## drying

air drying at 20°C



20 – 30 minutes

## sanding



For putties

first sanding: dry with P80 – P120

final sanding: dry with P180 – P240

### \*PICTUREGRAPH LEGENDA

- 2004/42** Reference to the CE law  
**IIBb** Annex, Table and Category of product  
**(250)** Limit value of VOC with reference to the category of product  
**250** Maximum VOC content of the product ready for the use

150315

*The information given in this technical data sheet is based on present scientific and technical knowledge and thus do not exempt the customer to test the suitability of our products for the use and for the intended purposes.*

**EP vernici s.r.l.**

Via Roma,12 I-48027 Solarolo (RA) tel.+39 0546 53322 fax +39 0546 53323 email: laboratorio@epvernici.it [www.epvernici.it](http://www.epvernici.it)

