

ACRYCLEAR HS EXTRA FAST ZA 700

*



**2004/42/IIB
e(840)585**

ACRYCLEAR HS EXTRA FAST ZA 700 is a 2K acrylic ANTI-SCRATCH extremely fast air-drying clearcoat (AIR DRY technology), that is compliant with 2004/42/EC directive.

Thanks to its features it is recommended for:

- fast repair without using oven
- spot and large repair
- application on water-based and on solvent-based base coats
- it has an excellent weathering and light resistance
- it shows no lins effect

use

mixing ratio



2 : 1 by volume with

ACRYDUR ST QA 2006/QA 2044

ACRYDUR FAST QA 2007

pot – life

2 hours at 25°C

application



thinning

ready for use

application viscosity

16 seconds DIN4



nozzle

1,3 – 1,4 mm

application pressure

2 – 3 bar



number of coats

2

film thickness

40 – 50 micron

air drying

hardeners

QA 2006 ST
QA 2044 ST

QA 2007 FAST

air drying at 20°C



dust free

10 – 15 minutes

10 – 15 minutes

dry for handling

2 hours

60 minutes

oven drying

hardeners

QA 2006 ST



flash off time

10 – 15 minutes



drying

10 – 15 minutes at
40 – 50°C

* PICTUREGRAPH LEGENDA

2004/42 Reference to the CE law

IIBe IIBe Annex, Table and Category of product

(840) (840) Limit value of VOC with reference to the category of product

585 Maximum VOC content of the product ready for the use

220131

The information given in this technical data sheet is based on present scientific and technical knowledge and thus do not exempt the customer to test the suitability of our products for the use and for the intended purpose.

EP vernici s.r.l.

Via Roma,12 I-48027 Solarolo (RA) tel.+39 0546 53322 fax +39 0546 53323 email: laboratorio@epvernici.it www.epvernici.it

