

ACRYTHINNER

ACRYTHINNER is a sort of acrylic thinners particularly suitable to prepare paints for big surfaces and for spot repairs.

It can be used to adjust viscosity of all 2K acrylic products.

ACRYTHINNER X 16

It can be used in all 2K acrylic products for application at temperature between 18°C and 26°C.

Specific weight: 0,87 kg/l

VOC: 870 g/l

ACRYTHINNER FAST X 22

It can be used in all 2K acrylic products for application at temperature between 8°C e 18°C.

Specific weight: 0,86 kg/l

VOC: 855 g/l

ACRYTHINNER SLOW X 33

It can be used in all 2K acrylic products for application at temperature between 26°C e 36°C.

Specific weight: 0,89 kg/l

VOC: 887 g/l

ACRYTHINNER LAV. UNIVERSALE X 1000

Washing universal thinner for solvent based and for water based products

Specific weight: 0,81 kg/l

VOC: 814 g/l

ACRYTHINNER X 38

Acrylic thinner for 1K e 2K

Specific weight: 0,88 kg/l

VOC: 883 g/l

150315

The information given in this technical data sheet is based on present scientific and technical knowledge and thus do not exempt the customer to test the suitability of our products for the use and for the intended purposes.

EP vernici s.r.l.

Via Roma,12 I-48027 Solarolo (RA) tel.+39 0546 53322 fax +39 0546 53323 email: laboratorio@epvernici.it www.epvernici.it

