

**- product name :** FAST PLUS SPRO

**Product is compliant with 2004/42/CE directive**



car refinish

2004/42

IIBe(840)650

**pictogram legend**

**2004/42** Reference to the EC law

**IIBe** Annex, Table and Category of product

**(840)** Limit value of VOC with reference to the category of product

**650** Highest VOC content in product ready to be used

**IT CAN BE PRODUCED IN TINTING SYSTEM :**

**VSPRO BINDER** 70

**BPN** 30

**- general features**

Matt industrial nitro synthetic enamel with elevated outdoor resistance, suitable for aerosol bomb.  
Exceptionally fast drying.  
Good elasticity  
Excellent covering property

**- use**

It is suitable for retouching or partial painting of any manufactured or industrial equipment, in case a very fast drying combined with a good aesthetic appearance is requested.

**- recommended cycles**

In order to improve adherence on the support, it is necessary the application of FAST PLUS SPRO enamel over a primer or a nitro-resistant antirust paint.

**film appearance:** matt

**colour :** on demand

**on stock**

**number of components** 1

**typical thickness :** 20 – 30 micron

**theor.coverage :** min. 12,0 m<sup>2</sup>/l - max. 18,0 m<sup>2</sup>/l

**drying at 25°C. :**

**dust free** : 3 – 5 minutes

**touch free** : 20 – 25 minutes

**depth** : 40 – 60 minutes

**baking :**

**overcoating time :**

min. : wet on wet

- max. :

**shelf life :**

12 months at + 0/35°C.

**specific weight :** min. 1000 g/l - max. 1150 g/l

**solid content :** by weight = min. 45,5 % - max. 54,5 %  
by volume = min. 37,0 % - max. 40,5 %

The information given in this technical data sheet is based on present scientific and technical knowledge and thus does not exempt the customer from testing the suitability of our products for their intended purposes.